

Safety Data Sheet

Section 1 - Identification

Glomania UVI Paint / GLO-UVI-PAINT

Glomania

265 N Main St., STE D210
Kaysville, UT 84037

Phone (24h): (646) 838-1991

Prepared by: Regulatory Department

Product Use: Decorative water-based acrylic paint. White-bodied (visually neutral in daylight); fluoresces the named color under UV (blacklight) illumination.

Not recommended for: Professional Use Only. Not recommended for use by children. Not for skin, food-contact, or toy applications unless independently certified.

Variants covered: Red, Blue, Yellow, Orange, Green, White, Pink, Purple (8 color variants — each is white-bodied paint that fluoresces the named color under UV/blacklight; sold in 1oz, 2oz, 4oz, 8oz, and 1pt sizes)

Section 2 - Hazards Identification

GHS Ratings:

There are no GHS ratings that apply to this product at this time

GHS Hazards

There are no GHS hazards that apply to this product at this time

GHS Precautions

There are no GHS precautions that apply to this product at this time

Section 3 - Hazardous Composition

Chemical Name	CAS number	Weight Concentration %
Ammonium Hydroxide (28%) — pH adjuster, from acrylic base	1336-21-6	0.00% – 0.10%

Section 4 - First Aid

Inhalation: Remove subject to fresh air. Give artificial respiration if breathing has stopped. Seek medical attention.

Eye: Flush with water for 15 minutes. Remove contact lenses, if present and easy to do so. If symptoms develop and persist seek medical attention.

Skin: Wash with soap and water. Remove contaminated clothing. Seek medical attention for irritation.

Ingestion: If swallowed, dilute by giving 2 or more glasses of water to drink ONLY IF CONSCIOUS! Do not induce vomiting. Seek medical attention IMMEDIATELY.

Section 5 - Fire Fighting

Flash Point: 100 °C (212 °F)

LEL: N/A **UEL:** N/A

Extinguishing Media: Water, Foam, Carbon Dioxide, Dry Chemical, Powder. Do NOT use high pressure Water Spray, as this may spread the fire.

Unusual Fire and Explosion Hazards: Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. During a fire, irritating and highly toxic gases and/or fumes may generate during combustion or decomposition.

Hazardous Byproducts: Combustion will yield oxides of carbon and nitrogen, as well as monomer fume.

Fire Fighting Procedures: Move containers promptly out of fire zone. If removal is impossible, keep containers cool with water spray. Remain upwind and avoid breathing smoke or fumes.

Special Precautions: Wear self-contained breathing apparatus and full protective gear.

Section 6 - Release

Personal precautions, protective equipment and emergency procedures: Appropriate protective equipment must be worn when handling a spill of this material. See Section 8 - Exposure Control for recommendations. If exposed to material during clean-up operations, see Section 4 - First Aid for actions to follow.

Environmental precautions: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Methods and materials for containment and clean-up: Evacuate personnel to safe areas. Ventilate the area to dissipate vapor. Floor may be slippery; use care to avoid falling. Soak up spills with inert absorbent material. Sweep up and collect in suitable container for disposal. Avoid breathing vapor.

Section 7 - Handling

Precautions and safe handling: Use only in well-ventilated areas. Avoid inhalation of vapors/spray and contact with skin and eyes. Wear appropriate personal protective equipment. Read label before use.

Conditions for safe storage: Store in a cool, well-ventilated place. Keep out of the reach of children.

Section 8 - Exposure Control

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Ammonium Hydroxide (28%) 1336-21-6	TWA 35 mg/m ³ PEL, 50 ppm	TWA 18 mg/m ³ TLV, 25 ppm	Not Established

Engineering Controls: Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of possible vapor. Provide easy access to water supply, eye wash or emergency shower.

General Hygiene Considerations: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Private clothes and work clothes should be kept separate.

Personal Protective Equipment: None required under normal use. For techniques requiring continual hand exposure, gloves are recommended. Safety glasses or goggles recommended when spraying.

Section 9 - Properties

Properties listed are typical and not to be used as a specification.

Appearance: Liquid, color varies by variant	Odor: Typical of acrylic emulsion
Vapor Pressure: ≈ 5 mmHg	Odor threshold: Not available
Vapor Density: ≈ 4 (air = 1)	pH: 8.0 – 8.4
Density: 1.0 – 1.3	Melting point: Not applicable
Freezing point: Not available	Solubility: Miscible with water
Boiling range: ≈ 100 °C	Flash point: 100 °C (212 °F)
Evaporation rate: Not available	Flammability: Not flammable as supplied
Explosive Limits: N/A	Partition coefficient: Not available
Auto ignition temperature: Not available	Decomposition temperature: > 200 °C
Viscosity: Medium-bodied (< 3000 cP @ 25 °C)	VOC g/L less water: ≈ 128

Section 10 - Reactivity

Under normal conditions this mixture is considered to be: **STABLE**

Materials that are known to be incompatible with this mixture and should be avoided: Not Applicable

Risk of hazardous decomposition: Not Applicable

Hazardous polymerization will not occur.

Section 11 - Toxicology

Mixture Toxicity

Inhalation Toxicity LC50: 156 mg/L (estimated, based on acrylic-emulsion mixture data)

Component Toxicity

Ammonium Hydroxide (28%) [CAS 1336-21-6] — Oral LD50: 350 mg/kg (RAT)

Possible routes of entry or exposure: Not Applicable

Possible target organs of exposure to this mixture: Not Applicable

Effects of Overexposure

Carcinogenicity: This mixture as a whole has not been tested. No components are reported as known or possible carcinogens above reporting thresholds.

Section 12 - Ecological Toxicity

Ecotoxicity: This mixture as a whole has not been tested to determine its ecological toxicity.

Section 13 - Disposal

Disposal Instructions: Dispose as per local regulations. It is best to use all material, rather than dispose of it. If necessary, dispose of as latex paint.

Section 14 - Transport

Agency	Proper Shipping Name	UN Number	Packing Group	Hazard Class
DOT	Not Regulated			
IATA	Not Regulated			
IMDG	Not Regulated			

Section 15 - Regulatory

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

Not Applicable

Country	Regulation	All Components Listed
AUSTRALIA	AICS- Australian Inventory of Chemical Substances	Yes
CANADA	Domestic Substances List (DSL) and Non-Domestic Substance List (NDSL)	Yes
EUROPE	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
EUROPE	European List of Notified Chemical Substances (ELINCS)	No
JAPAN	Inventory of Existing and New Chemical Substances (ENCS)	No
CHINA	Inventory of Existing Chemical Substances in China (IECSC)	Yes
KOREA	Korean Existing Chemicals Inventory (KECI)	Yes
NEW ZEALAND	New Zealand Inventory of Chemicals (NZIoC)	Yes
PHILIPPINES	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
USA	Active-Toxic Substances Control Act (TSCA) Inventory	Yes

Section 16 - Other Information

While Glomania believes the data set forth herein is accurate as of the date hereof, Glomania makes no warranty with respect to the accuracy of this data and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation, and verification.

Date revised: 2026-05-08 **Reviewer Revision:** 1

Date Prepared: 2026-05-08